



EKON GRADE	PE300	PP-H
Raw material	HDPE	PP-H
Thickness Standard colours	0,8 - 12 mm Black Other colours on request.	0,8 - 10 mm Grey RAL 7032 Other colours on request.
Surface	Smooth/matt Smooth	Smooth
Option upper side (up to max 10 mm)	Grain structure	Grain structure
APPLICATIONS		
Properties	Sheet for many different construction applications. Suited for thermoforming and tankbuilding.	Grade with higher stiffness and better temperature resistance. Suited for constructions.
Working possibilities		
Sawing / drilling / routing	x	x
Bending / setting	x	x
Die-cutting	x	
Welding	x	x
Thermoforming	x	
DIMENSIONS SHEETS		
Standard dimensions	3.000 x 1.500 mm 2.000 x 1.000 mm	3.000 x 1.500 mm 2.000 x 1.000 mm
	Other dimensions are available on request.	
Maximum width	2200 mm	2200 mm
Maximum length	6000 mm	6000 mm
OPTIONS		
Protection film (1 or 2 sides)	Sheets can be provided with a protection film, to prevent damage in the customers production process. The film is easy to remove.	
UV-stabilizer	Products can be provided with a UV-stabilizer for outside application.	
V.16.02-Rev.02		